

GemStone Retardant.

Waterbased Additive.

DESCRIPTION:

GemStone Retardant is a water-based additive that slows cementitious mixtures from kicking off, and increasing pot life, before application of the cementitious product.

RECOMMENDED FOR:

- < Gemstone Spray mix and T-mix.
- < Gemstone Diamond Deck, Diamond Deck Dark, and Acrylic spray decks.
- < Gemstone Flexcoat.

FEATURES:

- Slows kick off times.
- Increase pot life.
- Increased application window.

PACKAGING / ESTIMATING:

GemStone Retardant is packaged in quart (32 oz) cylinders and one gallon (128 oz) containers.

PHYSICAL DATA:

Non-Flammable:

Specific Gravity:(H₂O = 1 @ 20E C)	1.2
% NonVolatile by Volume:	50.0
Boiling Point :	>212° F

TECHNICAL DATA:

Diluent	Water
Clean - Up	Water
Appearance and color:	Clear liquid Slight odor

STORAGE AND SHELF LIFE:

GemStone Resin has a shelf life of 6 months if stored in original, unopened containers between 40E to 90E F.(6E to 32E C). GemStone mix resin must be kept from freezing.

APPLICATION:

Add straight to coating mixture. Mix until thoroughly dispersed. (approx. 1 minute)

LIMITATIONS:

- < GemStone Retardant should be thoroughly dispersed into coatings mixtures.
- < Keep from freezing.
- < If skin contact occurs, clean with warm water and soap. For eyes, flush with clean water immediately for minimum 15 minutes and repeatedly. Seek medical attention immediately. Refer to Material Safety Data Sheet (MSDS) for further information.

RELATED BULLETINS:

MSDS - GemStone Retardant-19